

Transport conveyor **TB**



Operating principle

For the transportation of all processed products, and peeling waste, commensurate with customer specification and factory application.

The drive of the transport conveyors can be by means of motor gearbox or drum motor. The conveyor belt can be simply adjusted (tracked) on both sides of the frame.

Optionally the conveyor can be provided with a quick-release system for cleaning purposes.

All transport conveyors can be provided with approved food quality belts in blue, white or open (Intralox)™ type segmented belts or plastic wire mesh belt.

Flat conveyor belts are used for horizontally moving products. Elevator belts can be also be provided with flighted belts to integrate onto the flat conveyors. This type of belt is manufactured with a product holding hopper.

Transportation of wet product can be customised for clients individual requirements e.g. to include product re-arrangers, vacuum water extraction or air knife removers.

Features

- easy belt tracking
- easy belt tightening
- conveyor belt easy exchangeable
- long shelf life
- hygienic design (easy to clean and disinfect)
- extremely durable, hard-wearing and reliable

Options

- quick-release system
- infeed hopper
- belt beater
- drum motor drive
- spraying system
- movable execution
- customised belt sizes



Product specification

The transport conveyor TB is used for all processed products, and peeling waste, commensurate with customer specification and factory application.

Technical data

Type	TB
Voltage	230/400 V, 50/60 Hz
Installed power	depending on execution
Dimensions (LxWxH)	depending on execution

Sormac B.V.

P.O. Box 419
NL-5900 AK Venlo
Huiskensstraat 68
NL-5916 PN Venlo

T: +31 (0)77 351 84 44
F: +31 (0)77 320 48 01
info@sormac.nl
www.sormac.nl

Subject to changes